



PS-24E ADAPTER USER MANUAL AND WARRANTY



.Compitable with regulation of AEEE

PS-24E ADAPTER

USER MANUAL

We thank you for choosed Multitek PS-24E ADAPTER. Bu This user manual includes devices features for using efficiently.

MULTITEK PS-24E ADAPTER UNDER WARRANTY OF 2 YEARS FOR MANUFACTURING DEFECTS

THIS ADAPTER LIFETIME IS 5 YEARS.

Multitek has right to changes any features of products without informing other parties.

1-SECURITY WARNINGS:

For device and your safety some of security rules must be followed.

- Read meticulously user manual
- Read security warnings carefully

Points to consider during, storage, transportaion,carrying,

- Keep inside box while carry or transport for prevent psychical damages.
- Do not put any heavy materials on product box which may damage to device.
- If the device is dropped, it may not work or has permanent damages.
- Overcold or overhot atmosphere may cause to deformation, it can reduce to electronic components lifetimes or cut operating.

Points to consider During usage in hazardous for human and environment health,

- Be aware of sharep edges on boxes While take out product inside box,Throw the box recycle bin decomposed for material type.

Product Maintenance,

- This product not required periodic maintenance, for maintenance or repair contact to authorised service.
- This product may be cleaned by dry cloth periodically,Prior to cleaning product, disconnect the adapter,be sure that cleaning materials do not include any resolvent.(fuel,thinner e.g)
- In case any electrical shock, do not use any cable other than original type.
- Do not put any foreign material inside to product or do not operate with any device that mayt cause electrical shock
- Any connection or installation except the auhtorised service stuff can cause to damages.
-

Points to consider of energy consuming,

- Product was designed for 7/24 operating. Therefore if you use shorter period, It is reccommended that devices should be disconned from socket. Terminals keep operating improperly are wasting energyi, Be advised that terminals should be kept shut.

Please contact to service in case troubleshooting.

FEATURES

- Model : PS-24E ADAPTÖR
- Operating voltage : 100-240V AC,
- Operating current : 1.5A (Max)
- Output Voltage : +24VDC
- Current : 2.5A (Max.)
- Ripple and noise : output voltage max %1
- Operating Temperature : -5°, +55°
- Humidity : %90 (Yoğunlaşmamış)

OPERATING AND CONNECTION OF DEVICE

1-Green led is on when device is connected to power supply (220 AC)

2- Pole in the adapter, red cable (+) and black cable is GND (-) Adaptör ucundaki Kırmızı kablo (+) Siyah kablo GND (-)

3- Adapter has shortcut circuit protection.

